

WAVE POWER LL 0W-20

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER LL 0W-20 is a fully synthetic fuel saving long life oil based for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

Remark: This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.

WAVE POWER LL 0W-20 is formulated with high quality 100% Poly Alpha Olefin (PAO) base stocks in combination with an unique additive technology to achieve the following performance:

- Exceptional good low temperature properties.
- Excellent protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Improved fuel economy

WAVE POWER LL 0W-20 exceeds the following performance criteria:

VW 508 00/509 00 ACEA C5

Typical Analysis

Properties	Unit	Method	Typical Value
Colour		Visual	Green
SAE Grade		SAE J300	0W-20
Density @15 °C	kg/m ³	ASTM 4052	835
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	39
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.8
Viscosity Index		ASTM D2270	177
Viscosity CCS @ -35 °C	cP	ASTM D5293	3280
Flash Point COC	°C	ASTM D92	>205
Pour Point	°C	ASTM D7346	-45
Total Base Number	mgKOH/g	ASTM D2896	6.7
Sulphated Ash	%Wt	ASTM D874	0.79
Date Issued: 26-06-2017	Supersedes: -	Revision Nr.: -	

