

WAVE POWER SL 10W-40

Semi Synthetic Passenger Car Engine oil

WAVE POWER SL 10W-40 is a universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. **This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).**

WAVE POWER SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index

WAVE POWER SL 10W-40 exceeds the following performance criteria:

Approved MB-Approval 229.1 VW 501.01/505.00

Exceeds API: SL/CF ACEA A3/B3 BMW LL-01

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m ³	ASTM 4052	861
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	91
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	163
Viscosity CCS @ -25°C	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	%Wt	ASTM D874	0.95
Date Issued: 07-10-2016	Supersedes: 28-12-2015	Revision Nr.: 2	

