

WAVE POWER SF 20W-50

Mineral Passenger Car Engine oil

WAVE POWER SF 20W-50 is a multi-functional mineral engine oil for older gasoline-, diesel- and LPG engines of passenger cars and light vans with or without turbo compressor.

WAVE POWER SF 20W-50 is formulated on high performance virgin base stocks in combination with selected additive package to reach the following properties:

- Stable Viscosity Index.
- Good protection against rust, corrosion and wear.
- Good dispergency and detergency properties.
- Good antifoam properties.

WAVE POWER SF 20W-50 meets the following performance criteria:

API SF/CD

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m ³	ASTM 4052	887
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	173
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	18.9
Viscosity Index		ASTM D2270	122
Viscosity CCS @ -15°C	cP	ASTM D5293	9500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
Total Base Number	mgKOH/g	ASTM D2896	5.2
Date Issued: 28-12-2015	Supersedes:		Revision Nr.: 1

