

KOPR-KOTE®

TOOL JOINT & DRILL COLLAR COMPOUND

DESCRIPTION

KOPR-KOTE® drill collar and tool joint compound is a premium-quality, unleaded compound containing copper flake, graphite, and other natural extreme pressure and anti-wear additives. **KOPR-KOTE's** solids package is formulated to prevent excessive circumferential makeup by increasing the coefficient of friction under compressive forces. As stress levels rise above 50% of yield, the friction factor increases, limiting downhole makeup. Full hydraulic joint efficiency is maintained allowing joint shoulder faces to mate completely without standoff or deformation. **For invert or high-pH muds, use Jet-Lube EXTREME™.**

- **Not classified as marine pollutant - DOT Approval CA2004080025**
- NSF Registered H2 (No. 120923)
- Contains no lead or zinc.
- Extreme pressure additives provide additional protection against seizing and galling and allow consistent make-up.
- Aluminum complex grease base protects against rust and corrosion.
- Sticks to wet joints.
- Unequaled resistance to makeup downhole.
- Available in Arctic, Thermal and Specialty grades.
- Approved by NAM/Shell for under-balanced drilling applications.
- Conforms to assembly bill 1953

SERVICE RATING:
0°F (-18°C) TO 450° (232°C)

PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	Petroleum
Dropping Point	450°F (232°C)
(ASTM D-2265)	
Specific Gravity	1.15
Density (lb/gal)	9.6
Oil Separation (ASTM D-6184)	<3.0
Wt. % Loss @ 212°F (100°C)	
Flash Point (ASTM D-92)	>430°F (221°C)
NLGI Grade	1
Penetration @ 77°F	310 - 330
(ASTM D-217)	
Copper Strip Corrosion	1A, typical
(ASTM D-4048)	
4-Ball (ASTM D-2596)	
Weld Point, kgf	800, typical

PACKAGING

Code No.	Container Size	Shipping Wt.
10023	1 gal.	11 lb.
10012	2 gal.	20 lb.
10015	5 gal.	52 lb.
10024	15 gal.	152 lb.
10029	50 gal.	514 lb.

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS



ReinhardOil.dk
Helleruplund Alle 8
DK-2900 Hellerup
Tel: +45 70 26 70 07
CVR 32659470
www.reinhardoil.dk

WATERWELL

WATERWELL

WATERWELL

WATERWELL

WATERWELL

JET-LUBE, INC.

MATERIAL SAFETY DATA SHEET

Product Name: **KOPR-KOTE®**
Chemical Family: Petroleum based lubricating grease
Use: Tool joint and drill collar compound/anti-seize (MIL-PRF-907E)/ jacking lubricant

Supplier:



ReinhardOil.dk
 Helleruplund Alle 8
 DK-2900 Hellerup
 Tel: +45 70 26 70 07
 CVR 32659470
 www.reinhardoil.dk

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Lubricating Grease	74868219	60	N/A	N/A	STEL:
Nonhazardous Blend	7782435/1317335	20-30	UN	UN	STEL: UN
	13776744/471341				STEL: UN
Metallic Copper	7440508	10	N/A	1mg/M ³	STEL: 2mg/M ³

Main Hazards-Health Effects

Eyes: May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled. **Ingestion:** May cause diarrhea.
Skin: For hypersensitive persons, may irritate the skin after prolonged periods of contact.

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

Extinguishing Media: Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.
Protective Equipment for Fire fighting: Self-contained breathing apparatus.

Personal Precautions: Wear gloves & protective overalls. **Environmental Precautions:** Do not allow it to enter drains. **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

Handling: No special handling precautions necessary. **Storage:** Do not store at elevated temperatures.

Respiratory Protection: None needed. **Hand Protection:** Protective gloves for hypersensitive persons.
Eye Protection: Glasses, if applied to parts in motion. **Body Protection:** Overalls.

Physical State: Semisolid paste **Color:** Copper/Bronze **Odor:** Petroleum **pH:** Neutral **Boiling Range/Point °F (°C):** <600 (316)
Melting Point °F (°C): 500 (260) **Flash Point (COC) °F (°C):** 430 (221) **Autoignition Temperature °F (°C):** >500 (260)
Explosive Properties: LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A
Vapor Pressure (kPa): <0.01 **Percent Volatiles:** Nil **Density (g/cm³):** 1.15 **Flammability:** Not flammable at ambient temperature.
OAR Value: N/A **Oxidizing Properties:** None **Water Solubility:** Nil **Vapor Density:** >5

Stability: Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing & copper reactive agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons & oxides of carbon, sulfur & nitrogen. Residue mainly comprised of soot & mineral oxides.

Acute Toxicity: Not known. **Irritancy-Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.
Genotoxicity: None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No IARC: No **OSHA:** No
EC Classification (67/548/EEC): No **Allergens:** None known. **LC-50:** 1.98gm/l—actual test data - mysidopsis bahia. **LD-50:** N/A

Possible Effects: In extreme cases, may generate oil fractions that could act as a marine pollutant. Occurrences of this nature are highly unlikely. **Behavior:** Relatively well behaved. Bioaccumulation potential nil.

Environmental Fate: Highly unlikely to cause widespread contamination. Nontoxic to marine or land organisms.

Product Disposal: Do not incinerate. Contact waste disposal company or local authority for advice.

Container Disposal: Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. Liner—see Product Disposal section above.

D.O.T.: Nonhazardous D.O.T. exception CA2004080025 **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous
Sea Transport (IMO & IMDG): Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous

Labeling Information: None needed **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.

S Phrases: N/A, as known. **Ozone Depleting Chemicals:** N/A **TSCA:** All components are listed. **TSCA 12B Components:** None

WHMIS (Canada): Not controlled. **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** This product contains in part raw material components subject to reporting. **SARA 311/312:** None **CERCLA:** Nonhazardous **RCRA Hazard Class:** Nonhazardous

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

Signature:
Prepared by: Donald A. Oldiges
Date Issued: February 12, 2009


As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

LEGEND	
I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	IX. PHYSICAL AND CHEMICAL PROPERTIES
II. COMPOSITION INFORMATION ON INGREDIENTS	X. STABILITY AND REACTIVITY
III. HAZARDS IDENTIFICATION	XI. TOXICOLOGICAL INFORMATION
IV. FIRST AID MEASURES	XII. ECOLOGICAL INFORMATION
V. FIRE FIGHTING MEASURES	XIII. WASTE DISPOSAL
VI. ACCIDENTAL RELEASE MEASURES	XIV. TRANSPORT INFORMATION
VII. HANDLING AND STORAGE	XV. REGULATORY INFORMATION
VIII. EXPOSURE CONTROL/PERSONAL PROTECTION	XVI. OTHER INFORMATION

HMIS SYMBOL

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PPI	B

NFPA SYMBOL



PERSONAL PROTECTION INDEX