

WAVE POWER GM 5W-30

Fully Synthetic Passenger Car Motor Oil

Product Description:

WAVE POWER GM 5W-30 is a fully synthetic motor oil for gasoline,- LPG- and diesel engines with or without turbo in passenger cars with high quality base stocks and additive technology.

WAVE POWER GM 5W-30 is developed to exceed the service fill requirements of most recent models of GM/Opel.

WAVE POWER GM 5W-30 offers very good protection against wear and has outstanding thermo-oxidative stability and good low temperature fluidity lubrication also at the longest lubricating oil intervals.

WAVE POWER GM 5W-30 is recommended for the latest models of GM/Opel vehicles requiring GM LL-A-025/GM LL-B-025 quality oils.

Specifications:

Exceeds: ACEA A3/B4, API SL/CF, MB 229.5, VW 502.00/505.00, BMW Longlife-01, Opel GM LL-A-025/LL-B-025

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	5W-30
Kinematic Viscosity @ 40°C	ASTM D7042	65.5 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11.4 mm ² /s
Cranking Viscosity @ -30°C	ASTM D5293	6095 mPa.s
Viscosity Index	ASTM D2270	165
Density @ 15°C	ASTM D4052	852 kg/m ³
Flash Point (COC)	ASTM D92	226°C
Pour Point	ASTM D97	-39°C
Total Base Number	ASTM D2896	9.9 mg KOH/g
Sulphated Ash	ASTM D874	1.24 wt%

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

