

STREAM POWER OTB 2T

2-stroke Outboard Engine Oil

Product Description:

STREAM POWER OTB 2T is a premium ashless 2-stroke lubricant developed for high powered water-cooled outboard engines fitted with oil-injection or premix systems.

STREAM POWER OTB 2T is formulated with the latest additive technology that helps in keeping the engine cleaner.

STREAM POWER OTB 2T is easy to mix and forms stable mixtures with gasoline also at lower temperatures.

STREAM POWER OTB 2T is suited for high powered 2-cycle water cooled outboard engines requiring an NMMA TC-W3® quality specification.

Specifications:		
Exceeds: NMMA TC-W3®		
Property:	Test Method:	Typical Values:
Kinematic Viscosity @ 40°C	ASTM D7042	46 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	7.5 mm ² /s
Viscosity Index	ASTM D2270	130
Density @ 15°C	ASTM D4052	867 kg/m ³
Flash Point (COC)	ASTM D92	96°C
Pour Point	ASTM D97	-33°C
Total Base Number	ASTM D2896	3.45 mg KOH/g

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

