

## ATF POWER DX III

### Automatic Transmission Fluid

#### Product Description:

ATF POWER DX III is a high quality universal fluid to be used in automatic transmissions, torque convertors and power steering of passenger cars, light vans and commercial vehicles. High quality base oils and special additives ensure improved resistance to oxidation, possesses better low temperature fluidity and shows improved frictional properties.

ATF POWER DX III exceeds the performance requirements of General Motors DEXRON® III specification and provides excellent shifting behaviour under all conditions.

ATF POWER DX III has excellent thermo-oxidative stability preventing the formation of undesirable deposits.

ATF POWER DX III is recommended for all vehicles of General Motors requiring DEXRON®-III quality fluids as well as in vehicles of Ford requiring so called MERCON® fluids.

<b>Specifications:</b>		
Exceeds: General Motors DEXRON®III, Ford MERCON®		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
Kinematic Viscosity @ 40°C	ASTM D7042	41.6 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	7.8 mm <sup>2</sup> /s
Brookfield Viscosity @ -40°C	ASTM D2983	<20000 cP
Viscosity Index	ASTM D2270	165
Density @ 15°C	ASTM D4052	852 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	>190°C
Pour Point	ASTM D97	-39°C

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

