

## SUPER TRACTOR POWER 10W-40

### Super Tractor Oil Universal (STOU)

SUPER TRACTOR POWER 10W-40 is a high quality universal semi synthetic based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. SUPER TRACTOR POWER 10W-40 is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF).

SUPER TRACTOR POWER 10W-40 is formulated on high refined solvent mineral and synthetic base stocks in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersansy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

**SUPER TRACTOR POWER 10W-40 exceeds the following performance criteria:**

**Engine Spec:** API CG-4/CF-4/CE/SF, MB 228.1, ACEA E3

**UTTO/STOU Spec:** JD J20C, J20D, J27, Ford M2C86B, 134D, Ford M2C159B, Case MS 1204, 6, 7, 9, MF M 1135/1139/1143/1144/1145, CAT TO-2, API GL-4, Allison C4 ZF TE-ML 06A, 06B, 06C, 07B, NH 82009201, 2, 3

**Hydrau. Spec:** Eaton M-2950S, Eaton I-280-S, Danfoss

Properties:	Test Method:	Unit	Typical Value:
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	877
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	57
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	145
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTMD97	-30
Total Base Number	mgKOH/g	ASTM D2896	10.6

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

