

Suniso GS Series.**3 GS 3,5 GS and 4 GS**▪ Description:

SUNISO GS oils are premium quality oils designed for use as refrigeration compressor lubricant, with traditional refrigerants. They are highly stable and are essentially wax free. They have long histories of satisfactory service in many types of equipment and are approved by most manufacturers for both factory fill and maintenance fill of their equipment.

▪ Application:

SUNISO GS oils can be used in virtually any installation regardless of compressor or evaporator temperatures. They are ideally suited for low temperature systems where evaporator temperatures are below -18°C including residential and commercial refrigeration and air-conditioning systems.

▪ Properties:

- Chemical stability to extend service life, reducing maintenance costs.
- Cleaner operation of the compressor with fewer deposits and failures due to valve sticking.
- Excellent low temperature performance with no wax deposits to plug the system.
- Approval by most major equipment manufacturers.

▪ Typical analysis :

	3GS	3.5GS	4GS
density / 15 °C	0.910	0.914	0.916
visc.at 40°C	30 cSt	43 cSt	55 cSt
visc.at 100 °C	4.4 cSt	5.3 cSt	5.9 cSt
flash point COC	168°C	175°C	179°C
pour point	-40°C	-37°C	-36°C
floc point	-54°C	-50°C	-48°C
colour	1.0	1.0	1.0
aniline point	74°C	76°C	77°C