

# SUNOCO



## Synturo Crown 5W20

### Description

Fully synthetic lubricating engine oil, especially developed for the lubrication needs of a number of American and East Asian car and van models.

### Application

Recommended for the modern type North American gasoline and LPG powered cars and vans. Particularly in case API SM and/or ILSAC GF-4 is being recommended. Also back serviceable in case of ILSAC GF-3 and API SJ/SL recommendations. Suitable for a number of East Asian car models.

### Specifications

- API SM
- ILSAC GF-4/GF-3
- Ford WSS-M2C930-A (service fill spec.)
- Applicable in case GM 6094M is required

### Properties

- Lower ash level, lower phosphor and sulphur, extending efficient life time of the car's emission control system while keeping up its efficiency.
- Good fluidity at low temperatures enhances cold start performance.
- Friction modifiers give fuel-economy & better performance, with lower CO2 Emission (1.1-2.3 % fuel economy compared to API SJ/SL oil).
- Engines keep internally extremely clean, extending the engine life time.
- High quality for stable, optimum performance and extended oil drain intervals with high resistance against thermal breakdown, oxidation and wear.

### Typical analysis :

Density at 15°C	0.853
Viscosity at 40°C / cSt	47
Viscosity at 100°C / cSt	8.3
Viscosity at -30°C / cP	5000
Viscosity index	155
Flash point °C	231
Pour point °C	-39
TBN mg KOH/g	7.7
Colour	2.5



Teknisk afdeling  
Sunoco Danmark  
ReinhardOil.dk  
Helleruplund Alle 8  
DK-2900 Hellerup  
CVR 32659470  
2009-09-30 SQ



**Pro Lube**

**reinhard oil**